

Powerful yet Thrifty



PS-3615/3615Q

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3615 Series features a 15" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3615/PS-3615Q

Specification	PS-3615	PS-3615Q	
Processor	Intel Apollo Lake N3350	Intel Apollo Lake J3455	
System Memory	DDR3L SO-DIMM x 1, max. 8GB		
Storage Device	M.2 connector (SATA Signal Only) x 1		
Power Supply	12V/	12V/40W	
OS Support	Window	Windows 10 loT	
Display & Touch			
LCD	15" TF	15" TFT LCD	
Resolution	1024	1024 x 768	
Touch	True-flat PCAP touch with multi-to	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
I/O & Expansion			
Serial Port	4, DB9 x 3 + RJ50 x 1, 5V/1	4, DB9 x 3 + RJ50 x 1, 5V/12V support on all COM ports	
Parallel Port	1, via optional conversion ca	1, via optional conversion cable through service window	
Standard USB Port	5, USB 3.0 x 2+ USB 2.0 x 2 (on l/	5, USB 3.0 x 2+ USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)	
PoweredUSB Port	Optional 24V x 1 + 1	Optional 24V x 1 + 12V x 3 via GEN8 base	
OTG USB	N _Z	N/A	
LAN Port	10/100/1	10/100/1000 Mb x 1	
Display Port	VGA x 1, 12V support	VGA x 1, 12V support for Posiflex monitors	
CR Port	1, control 2 CR via optional Y-ca	1, control 2 CR via optional Y-cable, supporting 24V cash drawer	
PS/2 Port	1, via optional conversion ca	1, via optional conversion cable through service window	
Audio	Buzzer x 1; Optional int	Buzzer x 1; Optional internal 2W speaker x 1	
Expansion Slot	M.2 slot x 1		
Physical Dimension			
Dimension (W x D x H in mm)	372 x 25	372 x 252.7 x 320	
Weight (N. W. in kg)	5.86		
Environmental			
Operating Condition	0°C - 50°C, 20%RH - 90	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition		-20°C - 70°C, 10%RH - 90%RH	
Built-in Options			
WiFi	M.2 WiFi∕	BT module	
Attachment Options			
POS Monitor	Non-touch TFT L	Non-touch TFT USB LCD: 7"/9.7"	
Line Display	2 x 20 rear-mount LCI	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display	
Attachment	-	MSR; iButton; RFID; Fingerprint Sensor; Keypad	

















Authorized Distributor / Reseller

^{*}Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

^{*}The product information and specifications are subject to change without prior notice.
*Please refer to the website for more attachment options.